

ASPERFLEX

CHARACTERISTIC AND USE:

- Light and dragging resistance. Ideal For irrigation and sprinkling.
- Useful for discharge and light suction of water.
- It is used in some cases for pneumatic transport of cereals and granulated materials.

COLOR: Orange and Yellow with white helix

WORK PRESSURE: 80 PSI AT 68°F

EMPTINESS PRESSURE: 0.80 ATM = 760 mm. Hg

MATERIAL: PVC.

WORK TEMP: From 14°F to 140°F.

SIZE: ¾", 1", 1¼", 1½", 2", 2½", 3", 3½", 4", 5", 6" & 8"

LENGTH: 100 ,60, 33ft.

PACKAGING: Coil with covering of plastic film



PRODUCCION DE MANGUERAS PLASTICAS NAM S.A. DE C.V.

Enedino R. Arévalo Lote. 5 Mza. 2 S/N, Parque Industrial Exportec II, Esq. Blvd. Aeropuerto,
Toluca, Edo. De México. C.P. 50200 TEL (722)2735020/21, (55)53975807

www.pmpnam.com

ASPERFLEX

SPECIFICATION TABLE						
PART NO.	I.D. (In.)	O.D. (In.)	THICKNESS (In.)	Ft/Coil	BENDING RADIO (In.)	WEIGHT/COIL (Lbs)
1061NA0750CS	3/4"	0.99	0.12	100.00	5	17.9
1061NA1000CS	1"	1.24	0.12	100.00	6	21.8
1061NA1250CS	1 1/4"	1.50	0.13	100.00	8	24.5
1061NA1500CS	1 1/2"	1.76	0.13	100.00	10	37.7
1061NA2000CS	2"	2.31	0.16	100.00	13	54.9
1061NA2500CS	2 1/2"	2.83	0.17	100.00	16	66.1
1061NA3000CS	3"	3.38	0.19	100.00	19	103.8
1061NA3500CS	3 1/2"	3.93	0.21	100.00	23	131.4
1061NA4000CS	4"	4.46	0.23	100.00	26	152.1
1061NA5000BS	5"	5.47	0.24	60.00	33	137.1
1061NA6000BS	6"	6.57	0.29	60.00	39	163.1
1061NA8000AS	8"	8.50	0.25	33.00	41	143.3



PRODUCCION DE MANGUERAS PLASTICAS NAM S.A. DE C.V.

Enedino R. Arévalo Lote. 5 Mza. 2 S/N, Parque Industrial Exportec II, Esq. Blvd. Aeropuerto,
Toluca, Edo. De México. C.P. 50200 TEL (722)2735020/21, (55)53975807

www.pmpnam.com