

GREENFLOW

CHARACTERISTIC AND USE:

- For **normal** duty applications in industry and agriculture. Suction and discharge of water and sewage.
- Conveyance of solids in granular forms.

COLOR: Olive Green.

WORK PRESSURE: 80 PSI AT 68° F

EMPTINESS PRESSURE: 0.80 ATM = 760 mm. Hg

MATERIAL: PVC.

WORK TEMP: From 14° F to 140° F.

SIZE: ¾", 1", 1¼", 1 ½", 2", 2 ½", 3", 3½", 4"

LENGTH: 100 ft.

PACKAGING: Coil with covering of plastic film



PRODUCCION DE MANGUERAS PLASTICAS NAM S.A. DE C.V.

Enedino R. Arévalo Lote. 5 Mza. 2 S/N, Parque Industrial Exportec II, Esq. Blvd. Aeropuerto,
Toluca, Edo. De México. C.P. 50200 TEL (722)2735020/21, (55)53975807

www.pmpnam.com

GREENFLOW

SPECIFICATION TABLE						
PART NO.	I.D. (In.)	O.D. (In.)	THICKNESS (In.)	Ft/Coil	BENDING RADIO (In.)	WEIGHT/COIL (Lbs)
1075VE0750CS	3/4"	0.96	0.11	100.00	5	17.0
1075VE1000CS	1"	1.22	0.11	100.00	6	22.2
1075VE1250CS	1 1/4"	1.48	0.11	100.00	8	27.4
1075VE1500CS	1 1/2"	1.73	0.12	100.00	10	29.8
1075VE2000CS	2"	2.31	0.14	100.00	13	52.9
1075VE2500CS	2 1/2"	2.81	0.16	100.00	16	61.7
1075VE 3000 CS	3"	3.37	0.18	100.00	19	93.0
1075VE 3500 CS	3 1/2"	3.88	0.19	100.00	23	121.7
1075VE 4000 CS	4"	4.45	0.22	100.00	26	162.0



PRODUCCION DE MANGUERAS PLASTICAS NAM S.A. DE C.V.

Enedino R. Arévalo Lote. 5 Mza. 2 S/N, Parque Industrial Exportec II, Esq. Blvd. Aeropuerto,
Toluca, Edo. De México. C.P. 50200 TEL (722)2735020/21, (55)53975807

www.pmpnam.com